



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

Electrical
Current rating: 1Amps/contact max.
Contact resistance: ≤ 20mΩ/contact
Isolation resistance: ≥ 1000MΩ at V=100V
Withstanding Voltage: 300V AC/minute

Material
Contact: Phosphor Bronze
Isolator: High Temperature, Thermoplastic UL94V-0
Operating temperature: Gold plated: -55°C to +105°C
 Tin plated: -40°C to +105°C

order information

B127150	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Insulator Height	Type	Packaging	Special Customer	
04~80	01= gold flash	34= H= 3.40mm	1= with peg B1	F= tape&reel with cap		
06~80	xx= on request	44= H= 4.40mm	2= without peg	E= tube&cap		
		xx= on request	3= with peg B2	xx= on request		

	Dual Row Female Header Straight SMT Type		
	PROJECTON		
	DATE	30.03.2017	
	DRAWN	MR	
	CHECKED	BR	
APPROVED	BR		
	UNIT:	SCALE:	SIZE:
	mm		A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.