

4

3

2

1





REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	22.03.17	MR

**Electrical**

Current rating: 1,5Amps/contact max.  
 Contact resistance:  $\leq 20m\Omega$ /contact  
 Isolation resistance:  $\geq 1000M\Omega$  at V=100V  
 Withstanding Voltage: 450V AC/minute

**Material**



Contact: Phosphor Bronze  
 Isolator: High Temperature, Thermoplastic UL94V-0  
 Operating temperature: Tin plated: -40°C to +105°C  
 Gold plated: -55°C to +105°C



order information

B200122	xx	xx	xx	xx
No. of Positions	Plating Option	Packaging	Special Customer	
04*80	01= gold flash	A= bag		
	xx= on request	C= tube		
		xx= on request		

Recommended P.C.B Board Hole Layout



	<b>PROJECTON</b>		<b>Dual Row Female Header Right Angle Type</b>		
	<b>DATE</b>	22.03.2017	Customer Drawing-No.:		
	<b>DRAWN</b>	MR	Drawing-No.: 2160842		
	<b>CHECKED</b>	BR			
	<b>APPROVED</b>	BR	<b>UNIT:</b> mm	<b>SCALE:</b>	<b>SIZE:</b> A4

Tolerance:  
 X. ±0.50  
 .X ±0.35  
 .XX ±0.25  
 .XXX ±0.05  
 X\* ±2\*