



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	28.06.19	MR

Technical Specification:

Electrical
 Current rating: 1,5Amps/contact max.
 Contact resistance: 20 mΩ Max.
 Insulation resistance: 1000 MΩ min.
 Withstanding Voltage: 450V AC/minute

Material
 Contact: Brass
 Insulator: High Temperature, Thermoplastic UL94V-0
 Operating temperature: -55°C to +105°C

order information

B200150	XX	XX	XX	XX	XX	XX
No. of Positions	Plating Option	Type	Packaging	Dimension	Special Customer	
04~80	01= gold flash xx= on request	1= with peg 2= without peg xx= on request	E= tube&cap F= tape&reel with cap xx= on request	D/ W1/ W2	xx= on request	

BRCONNECTORS Dual Row Female Header Straight SMT Type

Tolerance: X. ±0.50 .X ±0.30 .XX ±0.20 .XXX ±0.05 X° ±2°	PROJECTON		
	DATE	28.06.2019	Customer Drawing-No.:
	DRAWN	MR	Drawing-No.: 2162612
	CHECKED	BR	
	APPROVED	BR	
	UNIT:	mm	SCALE:
			SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.