

RoHS  
REACH  
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	22.03.17	MR



**Electrical**  
**Current rating:** 3Amps/contact max.  
**Contact resistance:** ≤ 20mΩ/contact  
**Isolation resistance:** ≥ 1000MΩ at V=100V  
**Withstanding Voltage:** 550V AC/minute

**Material**  
**Contact:** Phosphor Bronze  
**Isolator:** High Temperature, Thermoplastic UL94V-0

**Operating temperature:** Gold plated: -55°C to +105°C  
 Tin plated: -40°C to +105°C

**order information**

B254116	XX	XX	XX	XX	XX	XX
No. of Positions	Plating Option	Insulator Height	Packaging	Dimension	Special Customer	
04~80	01= gold flash xx= on request	50= H= 5.00mm 57= H= 5.70mm 85= H= 8.50mm xx= on request	A= bag C= tube xx= on request	A	xx= on request	



		<b>Dual Row Female Header Straight Type</b>		
<b>Tolerance:</b> X. ±0.50 .X ±0.35 .XX ±0.25 .XXX ±0.05 X* ±2°	PROJECTON		Customer Drawing-No.:	
	DATE	22.03.2017	Drawing-No.: 2160875	
	DRAWN	MR		
	CHECKED	BR		
APPROVED	BR	UNIT:	SCALE:	SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.