



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	22.03.17	MR

Electrical
Current rating: 1,5Amps/contact max.
Contact resistance: $\leq 20m\Omega$ /contact
Isolation resistance: $\geq 1000M\Omega$ at V=100V
Withstanding Voltage: 450V AC/minute

Material
Contact: Phosphor Bronze
Isolator: High Temperature, Thermoplastic UL94V-0

Operating temperature: Gold plated: -55°C to +105°C
 Tin plated: -40°C to +105°C

order information

B254127	-	xx	xx	xx	-	xx
No. of Positions		Plating Option	Packaging			Special Customer
02~40		01= gold flash	A= bag			
		xx= on request	C= tube			
			xx= on request			

	BRCONNECTORS		Single Row Female Header Right Angle Type			
	PROJECTON					
	DATE	22.03.2017	Customer Drawing-No.:			
	DRAWN	MR	Drawing-No.: 2160880			
	CHECKED	BR				
APPROVED	BR			UNIT: mm	SCALE:	SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.