

RoHS
REACH
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

Technical Spezifications

Insulator: Black glass filled polyester PPS+GF30
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3(C36000)
 Contact Clip (4 finger): Beryllium copper (C17200)
 Mating Pin Ø: 0.38 to 0.50mm
 Forces: (polished steel gauge Ø 0.41mm)
 Insertion: 0.5 N typ.
 Withdrawal: 0.2 N typ.
 Mechanical Life: Min. 500 cycles
 Rated Current: 1 A
 Contact Resistance: Max. 20mΩ
 Dielectric Steength: Min. 500V_{RMS}

order information

BP127102	-	XX	XX	XX	XX	XX
No. of Positions		Pin Plating Option	Clip Plating Option	Packaging	Special Customer	
04-100		100= tin	01= gold flash	C= tube		
		xx= on request	xx= on request	xx= on request		



	Dual Row Precision Female Header Straight Type		
	PROJECTON		
	DATE	30.03.2017	
	DRAWN	MR	
	CHECKED	BR	
APPROVED	BR		
	UNIT:	SCALE:	SIZE:
	mm		A4

Tolerance:
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 .XXX ±0.05
 X* ±2"