

RoHS  
REACH  
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

**Technical Spezifications**

Insulator: Black glass filled polyester PPS+GF30  
 Flammability: UL 94V-0  
 Sleeve: Brass CuZn36Pb3(C36000)  
 Contact Clip (4 finger): Beryllium copper (C17200)  
 Mating Pin Ø: 0.38 to 0.50mm  
 Forces: (polished steel gauge Ø 0.41mm)  
 Insertion: 0.5 N typ.  
 Withdrawal: 0.2 N typ.  
 Mechanical Life: Min. 500 cycles  
 Rated Current: 1 A  
 Contact Resistance: Max. 20mΩ  
 Dielectric Steength: Min. 500V<sub>RMS</sub>

**order information**

BP127103	xx	xx	xx	xx	xx
No. of Positions	Pin Plating Option	Clip Plating Option	Packaging	Special Customer	
09~150	100= tin	01= gold flash	C= tube		
	xx= on request	xx= on request	xx= on request		



	<b>Triple Row Precision Female Header Straight Type</b>	
	PROJECTON	
	DATE	30.03.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
Tolerance: X. ±0.50 .X ±0.30 .XX ±0.20 .XXX ±0.05 X* ±2"		Customer Drawing-No.: Drawing-No.: 2160924
		UNIT: mm SCALE: SIZE: A4