

RoHS
REACH
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

Technical Spezifications

Insulator: Black glass filled polyester PPS+GF30
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3(C36000)
 Contact Clip (4 finger): Beryllium copper (C17200)
 Mating Pin Ø: 0.38 to 0.50mm
 Forces: (polished steel gauge Ø 0.41mm)
 Insertion: 0.5 N typ.
 Withdrawal: 0.2 N typ.
 Mechanical Life: Min. 500 cycles
 Rated Current: 1 A
 Contact Resistance: Max. 20mΩ
 Dielectric Steength: Min. 500V_{RMS}

order information

BP127123	-	xx	xx	xx	xx	-	xx
No. of Positions		Pin Plating Option	Clip Plating Option	Packaging			Special Customer
06-150		100= tin	01= gold flash	C= tube			
		xx= on request	xx= on request	xx= on request			



	BRCONNECTORS		Triple Row Precision Female Header Right Angle Type			
	PROJECTON					
	DATE	30.03.2017	Customer Drawing-No.:			
	DRAWN	MR	Drawing-No.: 2160929			
	CHECKED	BR				
APPROVED	BR			UNIT: mm	SCALE:	SIZE: A4

A

D

C

B

D

C

B

4

3

2

1

4

3

2

1