

RoHS  
REACH  
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

**Technical Spezifications**

Insulator: Black glass filled polyester PPS+GF30  
 Flammability: UL 94V-0  
 Sleeve: Brass CuZn36Pb3(C36000)  
 Contact Clip (4 finger): Beryllium copper (C17200)  
 Mating Pin Ø: 0.40 to 0.66mm or 0.50SQ  
 Forces: (polished steel gauge Ø 0.46mm)  
 Insertion: 0.7 N typ.  
 Withdrawal: 0.4 N typ.  
 Mechanical Life: Min. 500 cycles  
 Rated Current: 3 A  
 Contact Resistance: Max. 10mΩ  
 Dielectric Steength: Min. 1000V<sub>RMS</sub>

**order information**

BP200108	xx	xx	xx	xx	xx	xx
No. of Positions	Pin Plating Option	Clip Plating Option	Length	Packaging	Special Customer	
02~80	100= tin xx= on request	01= gold flash xx= on request	080= L= 8.0mm 115= L= 11.5mm xx= on request	C= tube xx= on request		



	<b>Dual Row Precision Female Header Straight Type</b>	
	PROJECTON	
	DATE	30.03.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
Tolerance: X. ±0.50 .X ±0.30 .XX ±0.20 .XXX ±0.05 X" ±2"		Customer Drawing-No.: Drawing-No.: 2160953
UNIT: mm		SCALE: A4