

4



3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR




Technical Spezifications

- Insulator: Black glass filled polyester PPS+GF30
- Flammability: UL 94V-0
- Sleeve: Brass CuZn36Pb3(C36000)
- Contact Clip (4 finger): Beryllium copper (C17200)
- Mating Pin  $\phi$ : 0.40 to 0.56mm
- Forces: (polished steel gauge  $\phi$  0.43mm)
- Insertion: 2 N typ.
- Withdrawal: 1 N typ.
- Mechanical Life: Min. 500 cycles
- Rated Current: 3 A
- Contact Resistance: Max. 10m $\Omega$
- Dielectric Steength: Min. 1000V<sub>RMS</sub>

order information

BP254109	-	xx	xx	xx	xx	-	xx
No. of Positions		Pin Plating Option	Clip Plating Option	Packaging			Special Customer
02*64		100= tin	01= gold flash	C= tube			
		xx= on request	xx= on request	xx= on request			



Single Row Precision Female Header Straight Type

Tolerance:  
 X.  $\pm 0.50$   
 .X  $\pm 0.30$   
 .XX  $\pm 0.20$   
 .XXX  $\pm 0.05$   
 X\*  $\pm 2^{\circ}$

PROJECTON	
DATE	30.03.2017
DRAWN	MR
CHECKED	BR
APPROVED	BR

Customer Drawing-No.:  
 Drawing-No.: 2161000

UNIT: mm SCALE: SIZE: A4