

4



3

2

1



REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR




Technical Spezifications

- Insulator: Black glass filled polyester PPS+GF30
- Flammability: UL 94V-0
- Sleeve: Brass CuZn36Pb3(C36000)
- Contact Clip (4 finger): Beryllium copper (C17200)
- Mating Pin Ø: 0.40 to 0.56mm
- Forces: (polished steel gauge Ø 0.43mm)
  - Insertion: 2 N typ.
  - Withdrawal: 1 N typ.
- Mechanical Life: Min. 500 cycles
- Rated Current: 3 A
- Contact Resistance: Max. 10mΩ
- Dielectric Steength: Min. 1000V<sub>RMS</sub>

order information

BP254115	-	xx	xx	xx	xx	xx	xx
No. of Positions	Pin Plating Option	Clip Plating Option	Length	Packaging	Special Customer		
01~40	100= tin xx= on request	01= gold flash xx= on request	060= L= 6.0mm 070= L= 7.0mm 080= L= 8.0mm 090= L= 9.0mm 100= L= 10.0mm 110= L= 11.0mm 120= L= 12.0mm xx= on request	C= tube xx= on request			



	<b>Single Row Precision Female Header Straight Type</b>	
	PROJECTON	
	DATE	30.03.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
Tolerance: X. ±0.50 .X ±0.30 .XX ±0.20 .XXX ±0.05 X* ±2°		Customer Drawing-No.: Drawing-No.: 2161006
		UNIT: mm    SCALE:    SIZE: A4