

4


3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR




Technical Spezifications

- Insulator: Black glass filled polyester PPS+GF30
- Flammability: UL 94V-0
- Sleeve: Brass CuZn36Pb3(C36000)
- Contact Clip (4 finger): Beryllium copper (C17200)
- Mating Pin Ø: 0.7 to 0.9mm or 0.635SQ
- Forces: (polished steel gauge Ø 0.76mm)
  - Insertion: 1.2 N typ.
  - Withdrawal: 0.6 N typ.
- Mechanical Life: Min. 500 cycles
- Rated Current: 3 A
- Contact Resistance: Max. 10mΩ
- Dielectric Steength: Min. 1000VRMS

order information

BP254120	XX	XX	XX	XX	XX
No. of Positions	Pin Plating Option	Clip Plating Option	Packaging	Special Customer	
02~80	100= tin	01= gold flash	C= tube		
	xx= on request	xx= on request	xx= on request		



	<b>Dual Row Precision Female Header Straight Type</b>	
	PROJECTON	
	DATE	30.03.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
	UNIT: mm	SCALE: A4

Tolerance:  
 X. ±0.50  
 .X ±0.30  
 .XX ±0.20  
 .XXX ±0.05  
 X" ±2"