

RoHS
REACH
compliant


REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR

Technical Specifications

Insulator: Black glass filled polyester PPS+GF30
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3(C36000)
 Contact Clip (4 finger): Beryllium copper (C17200)
 Mating Pin ϕ : 0.7 to 0.9mm or 0.635SQ
 Forces: (polished steel gauge ϕ 0.76mm)
 Insertion: 1.2 N typ.
 Withdrawal: 0.6 N typ.
 Mechanical Life: Min. 500 cycles
 Rated Current: 3 A
 Contact Resistance: Max. 10m Ω
 Dielectric Strength: Min. 1000V_{RMS}

order information

BP254126	xx	xx	xx	xx	xx
No. of Positions	Pin Plating Option	Clip Plating Option	Packaging	Special Customer	
02~80	100= tin	01= gold flash	C= tube		
	xx= on request	xx= on request	xx= on request		



	PROJECTON		Dual Row Precision Female Header Straight Type		
	DATE	30.03.2017	Customer Drawing-No.:		
	DRAWN	MR	Drawing-No.: 2161016		
	CHECKED	BR			
	APPROVED	BR	UNIT: mm	SCALE:	SIZE: A4