

4



3

2

1

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	30.03.17	MR




Technical Spezifications

Insulator: Black glass filled polyester PPS+GF30
Flammability: UL 94V-0
Sleeve: Brass CuZn36Pb3(C36000)
Contact Clip (4 finger): Beryllium copper (C17200)
Mating Pin Ø: 0.40 to 0.56mm
Forces: (polished steel gauge Ø 0.43mm)
Insertion: 2 N typ.
Withdrawal: 1 N typ.
Mechanical Life: Min. 500 cycles
Rated Current: 3 A
Contact Resistance: Max. 10mΩ
Dielectric Steength: Min. 1000V_{RMS}
Complanariny SMD Terminations: Max. 0.1mm (measured on 25mm long connectors)

order information

BP254150	-	xx	xx	xx	xx	xx
No. of Positions		Pin Plating Option	Clip Plating Option	Packaging	Special Customer	
02~40		100= tin	01= gold flash	F= tape&reel with cap		
		xx= on request	xx= on request	xx= on request		



	BRCONNECTORS		Single Row Precision Female Header Straight SMT Type			
	PROJECTON					
	DATE	30.03.2017	Customer Drawing-No.:			
	DRAWN	MR	Drawing-No.: 2161023			
	CHECKED	BR				
APPROVED	BR			UNIT: mm	SCALE:	SIZE: A4

A

D

C

B

D

C

B

4

3

2

1