



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	22.05.17	MR

Technical Specification

Current Rating: 1A AC, DC
 Voltage Rating: 100V AC, DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 30mΩ
 Insulation Resistance: 500MΩ
 Withstanding Voltage: 500V AC/minute
 Material Pin: Phosphor Bronze
 Material: UL94V-0

Circuit No.	Dimensions		
	A	B	C
08P	7.00	11.55	11.95
14P	13.00	17.55	17.95
20P	19.00	23.55	23.95
30P	29.00	33.55	33.95

order information

C100403	xx	xx	xx	xx
No. of Positions	Plating Option	Packaging	Special Customer	
08-30	01= gold flash 100= tin	D= tape&reel xx= on request	xx= on request	

	Single Row Wafer SMT Type, Side Entry	
	PROJECTON	
	DATE	22.05.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
Customer Drawing-No.:	2161087	
UNIT:	SCALE:	SIZE: A4
mm		

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.