



RoHS  
REACH  
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	29.05.17	MR

**Technical Specification**

Current Rating: 1.5A AC, DC  
 Voltage Rating: 50V AC,DC  
 Temperature: -25°C to +85°C  
*high temperature:* -40°C to +105°C  
 Contact Resistance: 20mΩ  
 Insulation Resistance: 100MΩ  
 Withstanding Voltage: 500V AC/minute  
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions			
	A	B	C	D
02P	1.20	4.20	2.65	3.65
03P	2.40	5.40	3.85	4.85
04P	3.60	6.60	5.05	6.05
05P	4.80	7.80	6.25	7.25
06P	6.00	9.00	7.45	8.45

**order information**

C120401	-	xx	xx	xx	-	xx
No. of Positions	Plating Option	Packaging	Special Customer			
02~06	01= gold flash	D= tape&reel	xx= on request			
xx= on request	100= tin	xx= on request	xx= on request			



**Single Row Wafer  
SMT Type, Side Entry**

Tolerance: .X ± 0.25 .XX ± 0.15 .XXX ± 0.05	PROJECTON				
	DATE	29.05.2017	Customer Drawing-No.:		
	DRAWN	MR	Drawing-No.: 2161116		
	CHECKED	BR			
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.