

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	29.05.17	MR
	01	new order information	10.02.20	MH

Technical Specification



Current Rating: 1A AC, DC
 Voltage Rating: 200V AC, DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 20mΩ
 Insulation Resistance: 100MΩ
 Withstanding Voltage: 500V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0

Dimension:

A = (No. of Pos. - 1) x 1.25
 B = A + 3.00

order information

C125405	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Type	Entry	Packaging	Special Customer	
02~15	100= tin xx= on request	A2= THT	B2= side	A= bag xx= on request	xx= on request	



		Single Row Wafer THT Type, Side Entry		
Tolerance: .X ± 0.25 .XX ± 0.15 .XXX ± 0.05	PROJECTON			
	DATE	29.05.2017	Customer Drawing-No.:	
	DRAWN	MR	Drawing-No.: 2161129	
	CHECKED	BR		
APPROVED	BR	UNIT:	SCALE:	SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.