

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR
	01	add dimension	21.03.22	MH

**Technical Specification**

Current Rating: 1A AC, DC  
 Voltage Rating: 125V AC,DC  
 Temperature: -25°C to +85°C  
*high temperature:* -40°C to +105°C  
 Contact Resistance: 20mΩ  
 Insulation Resistance: 100MΩ  
 Withstanding Voltage: 500V AC/minute  
 Material Pin: Brass  
 Material: Thermoplastic, UL94V-0  
 Solder Tabs: Brass

**Dimension:**

A = (No. of Pos.-1) X 1.25  
 B = A + 6.40  
 C = A + 6.82  
 D = A - 1.25  
 E = A + 1.65

**order information**

C125407	-	xx	xx	xx	-	xx
No. of Positions	Plating Option	Packaging	Special Customer			
02~30	01= gold flash	A= bag	xx= on request			
xx= on request	100= tin	xx= on request	xx= on request			

	<b>PROJECTON</b>		<b>Single Row Wafer</b>	
	<b>DATE</b> 19.06.2017		<b>SMT Type, Side Entry</b>	
	<b>DRAWN</b> MR		Customer Drawing-No.:	
	<b>CHECKED</b> BR		Drawing-No.: 2161152	
<b>APPROVED</b> BR		UNIT: mm		SCALE: SIZE: A4

