

RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR


Technical Specification

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC,DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 10mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 800V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions					Circuit No.	Dimensions				
	A	B	C	D	E		A	B	C	D	E
2X02P	2.00	6.00	4.70	---	1.50	2X13P	24.00	28.00	26.70	22.00	5.00
2X03P	4.00	8.00	6.70	---	3.00	2X14P	26.00	30.00	28.70	24.00	5.00
2X04P	6.00	10.00	8.70	---	4.00	2X15P	28.00	32.00	30.70	26.00	5.00
2X05P	8.00	12.00	10.70	6.00	4.00	2X16P	30.00	34.00	32.70	28.00	5.00
2X06P	10.00	14.00	12.70	8.00	4.00	2X17P	32.00	36.00	34.70	30.00	5.00
2X07P	12.00	16.00	14.70	10.00	5.00	2X18P	34.00	38.00	36.70	32.00	5.00
2X08P	14.00	18.00	16.70	12.00	5.00	2X19P	36.00	40.00	38.70	34.00	5.00
2X09P	16.00	20.00	18.70	14.00	5.00	2X20P	38.00	42.00	40.70	36.00	5.00
2X10P	18.00	22.00	20.70	16.00	5.00	2X21P	40.00	44.00	42.70	38.00	5.00
2X11P	20.00	24.00	22.70	18.00	5.00	2X22P	42.00	46.00	44.70	40.00	5.00
2X12P	22.00	26.00	24.70	20.00	5.00						

order information

C200404	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Locking	Packaging	Special Customer	
04~44	01= gold flash	B2= side	F3= front	A= bag	xx= on request	
xx= on request	100= tin			xx= on request		
						xx= on request



	PROJECTON		Dual Row Wafer THT Type, Side Entry		
	DATE	19.06.2017	Customer Drawing-No.:		
	DRAWN	MR	Drawing-No.: 2161212		
	CHECKED	BR			
APPROVED	BR	UNIT: mm	SCALE:	SIZE: A4	

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.