



RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR

Technical Specification

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC,DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 10mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 800V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions					Circuit No.	Dimensions				
	A	B	C	D	E		A	B	C	D	E
2X02P	2.00	6.00	4.70	---	1.50	2X12P	22.00	26.00	24.70	20.00	5.00
2X03P	4.00	8.00	6.70	---	3.00	2X13P	24.00	28.00	26.70	22.00	5.00
2X04P	6.00	10.00	8.70	---	4.00	2X14P	26.00	30.00	28.70	24.00	5.00
2X05P	8.00	12.00	10.70	6.00	4.00	2X15P	28.00	32.00	30.70	26.00	5.00
2X06P	10.00	14.00	12.70	8.00	4.00	2X16P	30.00	34.00	32.70	28.00	5.00
2X07P	12.00	16.00	14.70	10.00	5.00	2X17P	32.00	36.00	34.70	30.00	5.00
2X08P	14.00	18.00	16.70	12.00	5.00	2X18P	34.00	38.00	36.70	32.00	5.00
2X09P	16.00	20.00	18.70	14.00	5.00	2X19P	36.00	40.00	38.70	34.00	5.00
2X10P	18.00	22.00	20.70	16.00	5.00	2X20P	38.00	42.00	40.70	36.00	5.00
2X11P	20.00	24.00	22.70	18.00	5.00	2X21P	40.00	44.00	42.70	38.00	5.00

order information

C200404	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Locking	Packaging	Special Customer	
04~40	01= gold flash	B1= top	F3= front	A= bag	xx= on request	
xx= on request	100= tin			xx= on request		
	xx= on request					



BRCONNECTORS

**Dual Row Wafer
THT Type, Top Entry**

Tolerance: .X ± 0.25 .XX ± 0.15 .XXX ± 0.05	PROJECTON				
	DATE	19.06.2017	Customer Drawing-No.:		
	DRAWN	MR	Drawing-No.: 2161214		
	CHECKED	BR			
	APPROVED	BR	UNIT: mm	SCALE:	SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.