



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR

Technical Specification

Current Rating: 4A AC, DC
 Voltage Rating: 125V AC,DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 10mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 1000V AC/minute
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.00	5.96	09P	16.00	19.96
03P	4.00	7.96	10P	18.00	21.96
04P	6.00	9.96	11P	20.00	23.96
05P	8.00	11.96	12P	22.00	25.96
06P	10.00	13.96	13P	24.00	27.96
07P	12.00	15.96	14P	26.00	29.96
08P	14.00	17.96	15P	28.00	31.96

order information

C200406	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Packaging	Special Customer	
02~15	01= gold flash	B1= top	A= bag	xx= on request	
xx= on request	100= tin		xx= on request		
			xx= on request		

	BRCONNECTORS		Single Row Wafer THT Type, Top Entry		
	PROJECTON		Customer Drawing-No.:		
	DATE	19.06.2017	Drawing-No.: 2161230		
	DRAWN	MR			
CHECKED	BR				
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.