



RoHS REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	04.07.17	MR

Technical Specification

Current Rating: 3A AC, DC
Voltage Rating: 300V AC, DC
Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
Contact Resistance: 20mΩ
Insulation Resistance: 100MΩ
Withstanding Voltage: 1000V AC/minute
Material Pin: Brass, Sn plated
Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions	
	A	B
02P	2.00	6.00
03P	4.00	8.00
04P	6.00	10.00
05P	8.00	12.00
06P	10.00	14.00
07P	12.00	16.00
08P	14.00	18.00
09P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00

order information

C200411	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Kinked	Packaging	Special Customer	
02~15	01= gold flash	B2= side	E1= Type 1	A= bag	xx= on request	
xx= on request	100= tin		E2= Type 2	xx= on request		

xx= on request

	PROJECTON		Single Row Wafer THT Type, Side Entry			
	DATE	04.07.2017	Customer Drawing-No.:			
	DRAWN	MR	Drawing-No.: 2161322			
	CHECKED	BR				
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4	
		mm				

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.