

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	04.07.17	MR








**Technical Specification**

Current Rating: 3A AC, DC  
 Voltage Rating: 500V AC,DC  
 Temperature: -25°C to +85°C  
*high temperature:* -40°C to +105°C  
 Contact Resistance: 20mΩ  
 Insulation Resistance: 100MΩ  
 Withstanding Voltage: 1500V AC/minute  
 Material Pin: Brass  
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions	
	A	B
02P	2.50	5.00
03P	5.00	7.50
04P	7.50	10.00
05P	10.00	12.50
06P	12.50	15.00
07P	15.00	17.50
08P	17.50	20.00
09P	20.00	22.50
10P	22.50	25.00
11P	25.00	27.50
12P	27.50	30.00
13P	30.00	32.50
14P	32.50	35.00
15P	35.00	37.50

**order information**

C250403	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Packaging	Special Customer	
02~15	01= gold flash	B1= top	A= bag	xx= on request	
xx= on request	100= tin		xx= on request		
			xx= on request		



	<b>BRCONNECTORS</b>		<b>Single Row Wafer THT Type, Top Entry</b>		
	PROJECTON		Customer Drawing-No.:		
	DATE	04.07.2017	Drawing-No.: 2161344		
	DRAWN	MR			
CHECKED	BR				
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4