

RoHS REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	03.08.17	MR


Technical Specification

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 20mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 1500V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions	
	A	B
03P	5.08	10.17
04P	7.62	12.71
05P	10.16	15.25
06P	12.70	17.79
07P	15.24	20.33
08P	17.78	22.87
09P	20.32	25.41
10P	22.86	27.95
11P	25.40	30.49
12P	27.94	33.03

order information

C254401	xx	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Type	Entry	Peg	Packaging	Special Customer	
02~12	01= gold flash	A1= smt	B1= top	C1= without	F= tape&reel with cap	xx= on request	
xx= on request	100= tin				xx= on request		
							xx= on request



PROJECTON

DATE 03.08.2017

DRAWN MR

CHECKED BR

APPROVED BR

Customer Drawing-No.:

Drawing-No.: 2161369

UNIT: mm

SCALE:

SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.