



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	03.08.17	MR

Technical Specification

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC,DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 20mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 1500V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions	
	A	B
02P	2.54	7.59
03P	5.08	10.13
04P	7.62	12.67
05P	10.16	15.21
06P	12.70	17.75
07P	15.24	20.29
08P	17.78	22.83
09P	20.32	25.37
10P	22.86	27.91
11P	25.40	30.45
12P	27.94	32.99

order information

C254401	xx	xx	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Type	Entry	Peg	Packaging	Special Customer	
02~12	01= gold flash	A2= tht	B2= side	C1= without	A= bag	xx= on request	
xx= on request	100= tin					xx= on request	
							xx= on request

	Single Row Wafer THT Type, Side Entry		
	PROJECTON		Customer Drawing-No.:
	DATE	03.08.2017	Drawing-No.: 2161367
	DRAWN	MR	
CHECKED	BR		
APPROVED	BR		
		UNIT: mm	SCALE:
			SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.