



RoHS  
REACH  
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	03.08.17	MR

**Technical Specification**

Current Rating: 3A AC, DC  
Voltage Rating: 250V AC,DC  
Temperature: -25°C to +85°C  
*high temperature:* -40°C to +105°C  
Contact Resistance: 20mΩ  
Insulation Resistance: 1000MΩ  
Withstanding Voltage: 1000V AC/minute  
Material Pin: Brass  
Material: Thermoplastic, UL94V-0

Circuit No.	Dimensions		
	A	B	C
02P	2.54	7.62	6.22
04P	7.62	12.70	11.30
05P	10.16	15.24	13.84
06P	12.70	17.78	16.38
08P	17.78	22.86	21.46

**order information**

C254403	xx	xx	xx	xx	xx
No. of Positions	Plating Option	Entry	Packaging	Special Customer	
02~08	01= gold flash	B2= side	A= bag	xx= on request	
xx= on request	100= tin	xx= on request			
xx= on request					

	<b>Single Row Wafer THT Type, Side Entry</b>	
	PROJECTON	
	DATE	03.08.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
Tolerance: .X ± 0.25 .XX ± 0.15 .XXX ± 0.05		Customer Drawing-No.:
		Drawing-No.: 2161377
		UNIT: mm
		SCALE:
		SIZE: A4