



REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR

Technical Specification

Current Rating: 1A AC, DC
Voltage Rating: 200V AC,DC
Temperature: -25°C to +85°C
high temperature: on request
Contact Resistance: 40mΩ
Insulation Resistance: 100MΩ
Withstanding Voltage: 500V AC/minute
Material: Thermoplastic, UL94V-0
Material Ground Plate: Stainless
Solder Tabs: Brass
Pin Material: Phosphor Bronze
Material Lock Leaver: Stainless

order information

D125409	xx	xx	xx	xx
No. of Positions	Special	Packaging	Special Customer	
31	E3= with latches	B= tray	xx= on request	
xx= on request		xx= on request		

	Dual Row Housing Straight Type With Latches		
	PROJECTON		
	DATE	19.06.2017	
	DRAWN	MR	
	CHECKED	BR	
APPROVED	BR		
	UNIT:	SCALE:	SIZE:
	mm		A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.