

RoHS REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	09.03.18	AT

Technical Specifications

Material

Screws: M2.5 Steel Zn plated
 Cage: Brass, Ni plated
 Pin header: Brass, Sn plated
 Housing: PA66, UL94V-0

Electrical


	UL	IEC
Rated voltage:	300V	250V
Rated current:	15A	17,5A
Wire range:	30-14AWG	1.5mm ²
Contact resistance:	20mΩ	
Insulation resistance:	500MΩ/DC500V	
Withstanding voltage:	AC2000V/1Min	

Mechanical

Temperature: -40°C to +105°C
 Max. soldering: +250°C/5 sec
 Torque: 0.4Nm/3.6Lbin
 Strip length: 6-7mm

order information

N50048	-	xx	xx	xx	xx
No. of Positions		Colour	Packing	Special Customer	
02~24		10=Green	A= bag		
		xx= on request	BO= Box		
			xx= on request		



variable range	linear dimension(Tolerances Standard GB/T 14486-2008)															
	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all	to 5	over 5 to 30	over 30 to 120	over 120 to	
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

		PCB Print Clamp	
PROJECTON		Allgemeintoleranz ISO 2768-m	
DATE	09.03.2018	Customer Drawing-No.:	
DRAWN	AT	Drawing-No.: 2161779	
CHECKED	MR		
APPROVED	BR	UNIT: mm	SCALE: SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.