



RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	04.02.19	MH

Technical Specifications

Material		
Screws:	M2.5 Steel Zn plated	
Cage:	Copper alloy, Sn plated	
Housing:	High Temperature, UL94V-0	
Electrical		
	UL B	IEC 3
Rated voltage:	300 V	250 V
Rated current:	15 A	24 A
Wire range:	30-14 AWG	2.5mm ²
Withstanding voltage:	1600 V AC/minute	
Mechanical		
Temperature:	-40°C to +105°C	
Max. soldering:	+250°C/5 sec	
Torque:	0.4 Nm/3.5 Lbin	
Strip length:	6-7mm	

order information

N50838	xx	xx	xx	xx
No. of Positions	Colour	Packing	Special Customer	
02~24	10=Green	BO= Box	xx= on request	
	xx= on request	xx= on request		

	BRCONNECTORS		PCB Print Clamp			
	PROJECTON					
	DATE	04.02.2019	Customer Drawing-No.:			
	DRAWN	MH	Drawing-No.: 2163667			
	CHECKED	MH				
APPROVED	BR	UNIT:	SCALE:	SIZE:	A4	

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.