



SECTION A-A

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	11.04.18	AT

Technical Specifications

Material

Screws: M2.0 Steel Zn plated
 Clamp: Phosphor bronze, Ni plated
 Wire guard: Brass, Ni plated
 Housing: PA66, UL94V-0

Electrical

Rated voltage:	300V	250V
Rated current:	8A	10A
Wire range:	28-16AWG	1.5mm ²
Contact resistance:	20mΩ	
Insulation resistance:	500MΩ/DC500V	
Withstanding voltage:	AC2000V/1Min	

Mechanical

Temp. Range: -40°C to +105°C
 Torque: 0.2Nm/1.7Lbin
 Strip length: 6-7mm

order information

Q35008	xx	xx	xx	xx
No. of Positions	Colour	Packing	Special Customer	
02*24	10=Green	A= bag		
	xx= on request	BO= Box		
		xx= on request		

variable range	linear dimension				fillet	chamfer	short angle sid				≡	-	□	//	⊥		
	to 6	over 30	over 120	over 480			to 6	to 10	to 50	to 120						to 5	to 30
tolerance	±0.1	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30°	20°	10°	0.5	0.025	0.06	0.12	0.4

	Plug-in Terminal Block		
	PROJECTON		Allgemeintoleranz ISO 2768-m
	DATE	11.04.2018	Customer Drawing-No.:
	DRAWN	AT	Drawing-No.: 2161855
	CHECKED	MR	
APPROVED	BR		
		UNIT: mm	SCALE: SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.