



SECTION A-A

RoHS REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	17.04.18	AT

Technical Specifications

Material

Screws: M2.0 Steel Zn plated
 Shrapnel: Brass, Ni plated
 Clamp: Brass, Ni plated
 Housing: PA66, UL94V-0

Electrical

Rated voltage:	300V	250V
Rated current:	8A	10A
Wire range:	26-16AWG	1.0mm ²
Contact resistance:	20mΩ	
Insulation resistance:	500MΩ/DC500V	
Withstanding voltage:	AC2000V/1Min	

Mechanical

Temp. Range: -40°C to +105°C
 Torque: 0.2Nm/1.7Lbin

order information

Q39602	-	xx	xx	xx	xx
No. of Positions		Colour	Packing	Special Customer	
02~24		10=Green	A= bag		
		xx= on request	BO= Box		
			xx= on request		

linear dimension(Tolerances Standard GB/T 14486-2008)												
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all	to 5
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5
											0.025	0.06
												0.12
												0.4

	Plug-in Terminal Block	
	PROJECTON	Allgemeintoleranz ISO 2768-m
	DATE	17.04.2018 Customer Drawing-No.:
	DRAWN	AT Drawing-No.: 2161943
	CHECKED	MR
APPROVED	BR	UNIT: mm SCALE: SIZE: A4