



SECTION:A-A

RoHS REACH compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	13.04.18	AT

Technical Specifications

Material

Screws: M3.0 Steel Zn plated
 Clamp: Phosphor bronze, Ni plated
 Cage: Brass, Ni plated
 Housing: PA66, UL94V-0

Electrical

Rated voltage:	300V	450V
Rated current:	15A	17.5A
Wire range:	28-14AWG	1.5mm ²
Contact resistance:	20mΩ	
Insulation resistance:	500MΩ/DC500V	
Withstanding voltage:	AC2000V/1Min	

Mechanical

Temp. Range: -40°C to +105°C
 Torque: 0.5Nm/4.5Lbin
 Strip length: 7-8mm

order information

Q50029	-	xx	xx	xx	-	xx
No. of Positions		Colour	Packing	Special Customer		
02~24		10=Green	A= bag			
		xx= on request	BO= Box			
			xx= on request			

linear dimension(Tolerances Standard GB/T 14486-2008)																
	≡	-	□	//	⊥											
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	all	to 5	over 5 to 30	over 30 to 120	over 120 to 120	
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

		Plug-in Terminal Block		
PROJECTON				
DATE	13.04.2018	Customer Drawing-No.:		
DRAWN	AT	Drawing-No.: 2161925		
CHECKED	MR			
APPROVED	BR	UNIT: mm	SCALE:	SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.