



RoHS
REACH
compliant

REVISION DATA				
SYM	REV	DESCRIPTION	DATE	APPR.
	00	new part	19.06.17	MR

Technical Specification

Current Rating: 4A AC, DC
 Voltage Rating: 125V AC, DC
 Temperature: -25°C to +85°C
high temperature: -40°C to +105°C
 Contact Resistance: 10mΩ
 Insulation Resistance: 1000MΩ
 Withstanding Voltage: 1000V AC/minute
 Material Pin: Brass
 Material: Thermoplastic, UL94V-0
 Material Solder Tabs: Brass

Circuit No.	Dimensions		
	A	B	C
04P	6.00	10.60	6.40
05P	5.00	11.60	8.40
06P	10.00	14.60	10.40
08P	14.00	18.60	14.40

order information

C200413	XX	XX	XX	XX	XX
No. of Positions	Plating Option	Type	Packaging	Special Customer	
04~08	01= gold flash	A2= tht	D= tape&reel	xx= on request	
xx= on request	100= tin		xx= on request		
			xx= on request		

	Single Row Wafer THT Type, Side Entry	
	PROJECTON	
	DATE	19.06.2017
	DRAWN	MR
	CHECKED	BR
APPROVED	BR	
	UNIT: mm	SCALE:
		SIZE: A4

Diese Zeichnung ist ausdrücklich Eigentum der BR-connectors GmbH. Ohne vorherige Zustimmung seitens der BR-connectors GmbH darf diese nicht vervielfältigt, noch an Dritte zugänglich gemacht werden. Wir behalten uns alle Rechte vor, auch im Falle einer Patentierung nach Gebrauchsmusterprüfung.